

Price Page

Jackson - Overhead Closers

Vendor Site

20101M01 - Overhead Concealed Closer

Application: aluminum doors exterior and interior

Features

- ½" spindle length
- Regular duty spring size
- Available in 90 and 105 degree swing hold or no hold options
- Dual valve closing control sweep and latch speeds are adjustable
- Cushioned tri-polymer backstop protects the closer
- Non handed
- Single or double acting
- · Suitable for both center hung and offset applications
- UL Listed, UL 228 (non-hold only)

Options

- 7/8" and 1-13/64" spindle lengths
- Extra Light, Light, and Heavy Duty Spring Sizes



Stocked Product

Item #	Description
20101M01	105 NH
20101M02	105 HO
20101M03	90 NH
20101M04	90 HO

20101M17 - Adjustable Spring Power Overhead Concealed Closer

Applications: ADA compliant entrances and where HVAC stack pressure is an issue

Features

- Meets ADA requirements
- Adjustable Spring Power for regulating opening force most accurately sizes 2-4
- Fully adjustable independent valves for sweep and latching functions
- Full ball bearing operation for increased efficiency
- Cushioned tri-polymer backstop protects the closer
- Non handed
- Single or double acting
- Suitable for both center hung and offset applications
- ½" spindle length
- UL Listed, UL 228 (non-hold only)

Options

- 7/8" and 1-13/64" spindle lengths
- End load arms
- Side load arms
- Bottom pivots
- ¾" off set and intermediate pivots
- Off set arms and slide tracks
- Mounting Clips



Item #	Description
20101M17	105NH
20101M18	105 HO
20101M19	90 NH
20101M20	90 HO



Price Page

Jackson - Overhead Closers

Vendor Site

20104M04 - Overhead Closer

Application: All glass herculite-type doors with patch or rail hardware and aluminum doors

Features

- Extended spindle 7/8" spindle length
- Regular duty spring size
- Available in 90 and 105 degree swing hold or no hold options
- Dual valve closing control sweep and latch speeds are adjustable
- Cushioned tri-polymer backstop protects the closer
- Non handed
- Single or double acting
- Suitable for both center hung and offset applications
- UL Listed, UL 228 (non-hold only)

Options

- ½" and 1-13/64" spindle lengths
- Extra Light, Light, and Heavy Duty Spring Sizes



Stocked Product

 Item #
 Description

 20104M01
 105 NH 7/8"

 20104M02
 105 HO 7/8"

20111MO - Grade 1 Overhead Concealed Closer w/hydraulic backcheck

Applications: Heavy traffic entrances and entrances with high wind conditions

Features

- Meets ANSI Grade 1 closer requirements
- Tested over 2 million opening and closing cycles
- Hydraulic backcheck protects the closer from wind gusts
- Fully adjustable independent valves for sweep and latching functions
- Full ball bearing operation for increased efficiency

Options

- 7/8" and 1-13/64" spindle lengths
- End load arms
- Side load arms
- Bottom pivots
- ¾" off set and intermediate pivots
- Off set arms and slide tracks
- Mounting Clips



Item #	Description
20111M01B	105 NH
20111M02B	105 HO

Price Page

Jackson - Center Hung Closer Accessories Vendor Site

202000 - End Load Arm for Top Rail

Features

- For 1" deep top rail
- Includes mounting hardware
- Forged steel



20219 - Mounting Clip Package

Features

- Mounting clip package
- Center Hung





20400B - Side Load Arm

Features

- For 1/2" deep top rail
- Includes mounting hardware
- Forged steel



Price Page

Jackson - Exits

Vendor Site

2086 - Concealed Vertical Rod Exit Device

Application: Narrow, Medium, Wide stile aluminum doors (min 1 3/4")

Features

- Handed Not reversible
- Dogging from inside manual operation or outside cylinder
- Optional cylinder dogging available
- Independent top and bottom bolt action with ½" throw
- Includes Humpback Top Strike TM to ensure secure closing
- Trigger action, positive bolt release
- Adjustable bolt guides allow bolt adjustment with door installed
- Concealed silencers quiet rod operation
- Field sizable to 30"
- Listed ANSI/UL 305 panic hardware and ANSI 156.3 Grade 1 panic hardware
- Available as an Electrified Unit 312086E requires 302616 power supply



Item #	Handing	Finish
2086L	LHR	313, 628
2086R	RHR	313, 628



Price Page

Jackson - Pivots

Vendor Site

201060 - Type P Pivot

Features

- For Floor Installation
- For 1-9/16" deep bottom rail



201570- GW Center Hung Pivot

Features

- For Floor Installation
- For 1-9/16" deep bottom rail





20902 - G Type Pivot

Features

- For floor installation
- For 1-1/2" deep bottom rail
- Height adjustable



20944 - Ge Type Pivot

Features

- For threshold installation
- For 1-1/2" deep bottom rail
- Height adjustable





Price Page

Jackson - Pivots

Vendor Site

34" Offset Intermediate Pivots

J-14 - Pivot Package

Features

- · For aluminum doors and frames
- Max weight 125lbs.
- Reversible non handed
- Jamb slot-in
- Extruded aluminum
- 5/8" vertical adjustment
- Full race ball-bearing and iolite bronze bushing
- Fully retractable pin for easy installation





Stocked Product

Part #DescritionFinish41J14S313Short LegDark Bronze41J14S628Short LegClear Aluminum

J-19 - Intermediate Pivot

Features

- For aluminum or metal doors and frames
- Max weight 150lbs.
- Full mortise Handed
- Made from aluminum
- Also available: 41J190HD
- Max weight 1,000lbs.
- Made from Brass or Bronze of Stainless Steel
- 5/8" vertical adjustment
- Full race ball-bearing and iolite bronze bushing
- Fully retractable pin for easy installation



Part #	Descrition	Finish	
41J190L313	Left	Dark Bronze	
41J190R313	Right	Dark Bronze	
41J190L628	Left	Aluminum	
41J190R628	Right	Aluminum	
	9		



Price Page

Jackson - Pivots

Vendor Site

34" Offset Pivot Package

Features

- For aluminum frames and doors up to 125lbs.
- Extruded or Cast aluminum
- · Full race ball-bearing and iolite bronze bushing
- Fully retractable pin for easy installation
- 1/8" vertical adjustment

Stocked Product

Oloonou i iouuoi				
	Item #	Descrition	Finish	
	41J25L313	Left	Dark Bronze	
	41J25R313	Right	Dark Bronze	
	41J25L628	Left	Aluminum	
	41J25R628	Right	Aluminum	



Stocked Product

Descrition	Finish
Left	Dark Bronze
Right	Dark Bronze
Left	Aluminum
Right	Aluminum
	Left Right Left



689628 - Non-Handed Offset Top and Bottom Pivot Set

For Use With 1-3/4" Aluminum Doors

The CRL J689 Offset Pivot Sets are designed to be used with standard 1-3/4 inch (44 millimeter) storefront aluminum doors weighing not more than 125 pounds (57 kilograms). These Pivots are perfect for new or retrofit applications. Finish: ALUMINUM





Price Page

Jackson - Panic Accessories

Vendor Site


301084 - Hump Back Strike™ package for Jackson top bolt exit devices

Product Description & Features

- · Prevents "bottom-bolt-drag"
- · Use with all Jackson top bolt panics
- · Ensures smooth, secure, action

Stocked Product

Item # 301084313 301084628 **Finish** Dark Bronze Aluminum



30821 - Mortise cylinder mountingpad for Jackson concealed vertical rod exit devices

Features

- For use with 1" outside cylinder
- Use MS type cam

Stocked Product

Item # 30821J313 30821J628 Finish Dark Bronze Aluminum





Price Page


Jackson - Offset Closer Accessories

Vendor Site

201134LC628

Features

- 201133 Forged Steel Offset arm
- 201129 slide track assembly for 5/8" shallow rail



201376 - Mounting "D" Clip Package - Special Mount



20900LC - Offset Arm Assembly

Features

- 20942 Forged Steel Offset Arm
- 20368 Slide Channel Assembly For 7/8" Deep Rail



20951 - Mounting "D" Clip Package - Offset Hung











Stocked Product
Finish 628