

## **ABS-AMERICAN BUILDING SUPPLY, INC.**

# Doormerica

## DC161 / DC161BF - Standard Duty Commercial Door Closer



### **Specifications:**

INCREASE

BACK CHECK

Adjusting Valve

Full rack and pinion type with cast aluminum alloy body. All closers shall be provided with non-critical valves adjustment to independently regulate the sweep, latch and back-check. Closer shall have full spring adjustment from size 1 to size 4 for barrier free (BF) size and size 2 to size 6 for standard size. The closer shall be pre-adjusted at the factory to size 2 for the DC161BF and size 3 for DC161. Closer shall be nonhanded with slim line cover with a projection of 3" from the surface of the door. All closers shall be mounted to allow the maximum degree of swing.

or DELAYED ACTION

Adjusting

Valve

Adjusting

#### Features:

- Same hole pattern as Norton 1600.
- Tri-Pack with regular, parallel and top-jamb mounting, instructions and full size template.
- Standard spring adjustment from size 2 to 6
- Non handed
- Standard with adjustable sweep, latch and back check.
- Slimline Plastic Cover
- SNB -Sex Nuts and Bolts

### **Options:**

- BF: Barrier free spring adjustment from size BF-4.
- H: Hold Open Arm

CAUTION: Door closer for Low Opening Force Applications: Door closers installed in openings required to meet the requirements of The Americans with Disabilities Act or ANSI/BHMA Standard

A117.1, when adjusted to meet those requirements, may not provide adequate closing power to dependably close and latch the door.









#### **CODE COMPLIANCE:**

- ANSI A156.4 Grade 1 UL10C and UBC 7.2 for positive pressure.
- ANSI A117.1 and ADA for barrier-free accessibility
- C-UBC -California Uniform Builders Code -2001
- California State Fire Marshall (CSFM) approved

#### 10 YEAR LIMITED WARRANTY

#### Stocked Product

ltem **Finish** Aluminum, Duro DC161 DC161BF Aluminum, Duro Aluminum, Duro DC161H



# ABS-AMERICAN BUILDING SUPPLY, INC.

# Doormerica

Power

## DC50 - Standard Duty Commercial Door Closer





- Tri-Pack with regular, parallel and top-jamb mounting. instructions and full size template.
- Standard Closer Spring Sized to 3, 4 with NO adjustment.
- Non handed
- Standard with adjustable sweep, latch.
- Slim line Plastic Cover
- SNB -Sex Nuts
- 10 year warranty
- 10 closers per shipping carton

### **Options:**

. BC: Backcheck adjustment valve





BACK CHECK

INCREASE



or DELAYED ACTION

Adjusting

#### **CODE COMPLIANCE:**

- ANSI A156.4 Grade 2. UL10C and UBC 7.2 for positive pressure.
- C-UBC -California Amended Uniform Builders Code -2001
- California State Fire Marshall (CSFM) approved
- NOTE: May need to consider other closer if barrier free required.
  Please discuss with sales associate.

#### 10 YEAR LIMITED WARRANTY

#### **Stocked Product**

Item	FIIIISII
DC53	Aluminum, Duro
DC54	Aluminum, Duro
DC54BC	Aluminum, Duro

## Closer Drop Plates (Drawings available upon request)

Closer used with	SKU	Description	Finish
DC40	PDC4018	Pull Side (Door Jamb)	AL/DU
DC40	PDC4018G	Push Side (Top Jamb)	AL/DU
DC40	PDC4018PA	Push Side (Door Mount)	AL/DU
DC40	PDC4018TJ	Push Side (Top Jamb)	AL/DU
DC70	PDC7018	DROP PLATE PULL SIDE MOUNT	AL/DU
DC70	PDC7018TJ	DROP PLATE TOP JAMB MOUNT	AL/DU
DC851	PDC8513146	Pull Side (Door Jamb)/Push Side (Top Jamb)	AL/DU
DC851	PDC8513148	Push Side (Top Jamb/Door Mount)	AL/DU
DC851	PDC8513546	Pull Side (Door Jamb)	AL/DU
DC851	PDC8513548	Push Side (Door mount)	AL/DU