




Doormerica

EDV701 / EDFV701 (Fire Rated)

Heavy Duty Grade 1 Vertical Rod Exit Device



Features:

- Chassis mounted unit construction.
- Minimum style 3-1/2".
- Standard door thickness 1-3/4".
- For all doors up to 36".
- Universal design retrofits on Von Duprin 9927 series & Sargent 88 Series.
- Material: Cover, and cap and rail are made of brass, bronze or Stainless Steel.
- 161 ANSI cutout.
- Mounting: Furnished with wood & machine screws. Thru bolts. standard on fire rated devices.
- Non Handed.
- Latch Bolt: Stainless Steel 3/4"
- Limited Lifetime Warranty

Specifications:

- All exit devices shall be of touch bar design with smooth operation and be operative over 2/3 of the door's clear opening width.
- All exit devices must be listed under "Panic Hardware" in the Accident Equipment List of Underwriter's Laboratories, Inc. Where labeled doors are used as exits, they must be equipped with labeled Fire Exit Hardware and UL 10C, UBC 7-2-1997 codes.
- All exit devices shall be of chassis mounted unit construction.

Dimensions:

Touchbar	Height to finish floor .. 41" at center
Touchbar	Projection
	Neutral 2-1/2"
	Depressed 1-3/4"
Center case 8-1/2" x 2-1/2" x 2"
Device length	Standard..... 2'2" to 3'
	Long (L) 2'9" to 4'
Top and Bottom latch case.....	3-15/16" x 2-1/8" x 1-3/8"
Fire Rated Bottom case.....	3-15/16" x 2-11/16" x 2-1/6"
Top and Bottom Rod length standard ...	Top Rod 50"
 Bottom Rod 36-1/4"
Top and Bottom Rod 48" x 96"	Top Rod 50"
	Bottom Rod 36-1/4"

Options:

- Stocked 48" x 96" length, specify "L"
- Available different functions. Lever escutcheon trims are Grade 1 construction with clutch free wheeling mechanism.
- Covers 161 cutout.
- Alarm Kit available for 3' & 4' applications.
- Glass Bead Kits available.



CODE COMPLIANCE:

- ANSI A165.3, Grade 1
- UL listed for Panic and UL 10C, UBC 7-2-1997 codes.
- UL listed for Fire Exit Hardware. 3 Hours.
- (A) label rating on pairs of doors up to 8'0" x 8'0" swinging in same or opposite directions.

LIMITED LIFETIME WARRANTY

Stocked Product

Item	Finish
EDV701	10B, 28, 32D 36"x 96", 48" x 96"
EDFV701*	10B, 28, 32D 36"x 96", 48" x 96"

* Fire rated



Doormerica

ED501 / EDF501 (Fire Rated)

Standard Duty Commercial Rim Exit Device



Features:

- Deadlatching and Non-Handed.
- Dogging Standard Only on NON-UL listed Device.
- Baked Enamel Aluminum (AL) and Duronodic (DU) Finish.
- For all doors up to 36".
- PEDPS01 & PEDSS01 -Standard Strike and Shim.
- PEDFP161 & PEDFP-ANSI -Latch & Strike Filler Plate.
- PEDSNB -Standard with Sex Bolts.
- EDF501 -UL Listed for Fire and Egress -Listed for 1-1/2 Hour for Doors Under 38" (3'-2") x 86" (7'-2").



CODE COMPLIANCE:

- ANSI A 156.3 Grade 2. UL 1 OC and UBC 7.2 for positive pressure.
- ANSI A 117.1 and ADA for barrier-free accessibility
- C-UBC -California Amended Uniform Builders Code -2001
- NFPA-80 -National Fire Protection Association 1999
- NFPA-101 National Fire Protection Association Life Safety -2000

Options:

- Stocked 48" length, specify "L" (for non rated device)
- EDS551 -Exit Device made from Stainless Steel.
- ALRMKIT500 -Alarm Kit. Mortise Cylinder NOT Included
- ETLHL500 -Entry Function -Lever -161 Cylindrical Prep.
- ETLHL580 -Storeroom Function -Lever -161 Cylindrical Prep.
- ETPP05 -Pull Plate with Cylinder cut-out, Rim Cylinder NOT Included.
- ETPP06 -Pull Plate Only.

1 YEAR LIMITED WARRANTY

Stocked Product

Item	Finish
ED501 (36" & 48")	Aluminum, Duro
EDF501*	Aluminum, Duro
EDS551	Stainless Steel
* Fire rated	




Doormerica

EDVR531 / EDFVR531 (Fire Rated)

Standard Duty Commercial Surface Vertical Rod Exit Device

Features:

- Deadlatching and Non-Handed. Dogging Standard Only on NON-UL listed Device.
- Interlocking Top and Pullman Bottom Latch.
- Baked Enamel Aluminum (AL) and Duronodic (DU) Finish.
- PEDPS03 & PEDPS11 -Standard Top & Bottom Strike.
- PEDFP161 & PEDFP-ANSI -Latch & Strike Filler Plate.
- PEDSNB -Standard with Sex Bolts.
- For all doors up to 36" (3') x 84" (7').
- EDFVR531 -UL Listed for Fire and Egress
-Listed for 1-1/2 Hour Fire doors under 38" (3'2") x 86" (7'2")



Options:

- ALRMKIT500 -Alarm Kit. Cylinder NOT Included, See Cylinder Section.
- ETLHL500 -Entry Function Lever #161 cylindrical preparation.
- ETLHL580 -Storeroom Function Lever #161 cylindrical Prep.
- ETPP05 Pull Plate with Cylinder cut-out, Rim Cylinder NOT Included.
- ETPP06 -Pull Plate Only.

CODE COMPLIANCE:

ANSI A 156.3 Grade 2. UL 1 OC and UBC 7.2 for positive pressure.
ANSIA117.1 and ADA for barrier-free accessibility
C-UBC -California Uniform Builders Code 2001
NFPA-80 -National Fire Protection Association 1999
NFPA101 National Fire Protection -Life Safety 2000

1 YEAR LIMITED WARRANTY

Stocked Product

Item	Finish
EDVR531	Alumnum and Duro
EDFVR531*	Alumnum and Duro
* Fire rated	



Doormerica

Mullion 7100 - For use with Non-Rated Rim Exit Devices on non-rated pairs of doors


Specifications:

Mullion Size 2" x 3" x 96" Steel Tube. Mullion may be field cut to fit proper size.
Rim Cylinder Use Rim Cylinder, cylinder not included. 3/8" spacer required. Not included.
Top Bracket Steel, using key allows the mullion to be removed in seconds.
Mullion can be locked in top bracket easily without using the key.
Bottom Bracket Steel, fixed by 4 hex bolts with Stainless Steel anchors.
Strike Use two standard Rim Strikes, not included
Finish Gray baked powder coating only


Mullion 7100F - For use with Fire-Rated Rim Exit Devices on fire-rated pairs of doors

Specifications:


Mullion Size 2" x 3" x 96" Steel Tube. Mullion may be field cut to fit proper size.
Rim Cylinder Use Rim Cylinder, cylinder not included. 3/8" spacer required. Not included.
Top Bracket Stainless Steel, using key allows the mullion to be removed in seconds.
Mullion can be locked in top bracket easily without using the key.
Bottom Bracket Stainless Steel, fixed by 4 hex bolts with Stainless Steel anchors.
Strike Use two (2) sets of Mullion Strikes (688) & Strike Hooks (689) - Not Included. (Part No. MULL7100FSTRIKEPACK)
Finish Gray baked powder coating only




The removable Mullion is used for with two Rim Devices on double doors.



FOR USE WITH FIRE-RATED



FOR USE WITH NON-RATED



Stocked Product

Item	Description
MULL7100	Mullion Non-Rated
MULL7100F	Mullion Fire-Rated
MULL7100FSTRIKEPACK	Fire Rated Mullion Pack